

Swivel Hoist Ring Specifications

Metric Model	Rated Load	Dimension mm							Weight (kg)
	WLL(T)	A	B	C	D	E	d	F	
M8X1.25-6g	0.4	27	39	85	38	33.3	7.9	12	0.27
M10X1.5-6g	0.5	27	39	85	38	33.3	7.9	19	0.27
M12X1.75-6g	1.05	35	58	135	65	54.3	12.7	19.1	1.2
M14X2.0-6g	1.05	35	58	135	65	54.3	12.7	31.8	1.2
M16X2.0-6g	1.9	35	58	135	65	54.3	12.7	31.8	1.2
M20X2.5-6g	2.15	40	67	160	75.5	64.3	19.1	38.1	2.21
M22X2.5-6g	2.25	40	67	160	75.5	64.3	19.1	38.1	2.21
M24X3.0-6g	4.2	40	67	160	75.5	64.3	19.1	38.1	2.21
M30X3.5-6g	5	50.8	95	205	90	74	22.2	50	3.86
M33X3.5-6g	7	50.8	95	205	90	74	22.2	50	3.86
M36X4.0-6g	8	50.8	95	205	90	74	22.2	54	3.86
M39X4.0-6g	8	50.8	95	205	90	74	22.2	58	3.86
M42X4.5-6g	10	63	108	230	100	85	25	63	6.08
M45X4.5-6g	10	63	108	230	100	85	25	68	6.08
M48X5.0-6g	10	63	108	230	100	85	25	68	6.08
M56X5.5-6g	15	70	120	278	132	95	32	84	10.8
M60X5.5-6g	15	70	120	278	132	95	32	90	10.8
M64X6.0-6g	15	70	120	278	132	95	32	95	10.8
M72	25	80	125	331	166	130	40	108	27
M90	35	80	125	331	166	130	40	135	31